

Strenx® 960 E/F

2025-05-22

The table shows available dimensions for direct order including the maximum length (mm).

Strenx® 960 E is available in thickness up to 120.0 mm and Strenx® 960 F is available in thickness up to 100.0 mm.

Some restrictions, contact your local sales representative for more information.

Outside the range of dimensions.

Minimum length: 2000 mm^{*)}

Minimum quantities:

Thickness: Minimum position weight:

3.0 - 60.0 2.5 tons

60.1 - 100.0 3.5 tons

100.1 - 120.0 4.0 tons

Width (mm)	1000-	1351-	1501-	1601-	1701-	1801-	1901-	2001-	2101-	2201-	2301-	2401-	2501-	2601-	2701-	2801-	2901-	3001-	3101-	3201-	3301-
Thickness (mm)	1350	1500	1600	1700	1800	1900	2000	2100	2200	2300	2400	2500	2600	2700	2800	2900	3000	3100	3200	3300	3350
3.0 - 3.9																					
4.0 - 4.7																					
4.8 - 5.7																					
5.8 - 6.0																					
6.1 - 6.7																					
6.8 - 7.7																					
7.8 - 8.7																					
8.8 - 10.0																					
10.1 - 25.0																					
25.1 - 26.0																					14600
26.1 - 27.0																				14200	14000
27.1 - 28.0																			14200	13700	13500
28.1 - 29.0																		14100	13700	13300	13100
29.1 - 30.0																	14100	13600	13200	12800	12600
30.1 - 31.0																14100	13600	13200	12800	12400	12200
31.1 - 32.0				Maximum length 14 630 mm											14200	13700	13200	12800	12400	12000	11800
32.1 - 33.0	14200													14200	13700	13300	12800	12400	12000	11600	11500
33.1 - 34.0	13800												14400	13800	13300	12900	12400	12000	11700	11300	11100
34.1 - 35.0	13400											14500	13900	13400	12900	12500	12100	11700	11300	11000	10800
35.1 - 36.0	13100											14100	13600	13100	12600	12200	11700	11400	11000	10700	10500
36.1 - 37.0	12700										14300	13700	13200	12700	12200	11800	11400	11100	10700	10400	10200
37.1 - 38.0	12400									14500	13900	13400	12800	12400	11900	11500	11100	10800	10400	10100	10000
38.1 - 39.0	12000									14200	13600	13000	12500	12000	11600	11200	10800	10500	10200	9800	9700
39.1 - 40.0	11700								14400	13800	13200	12700	12200	11700	11300	10900	10600	10200	9900	9600	9500
40.1 - 45.0	10400						14100	13400	12800	12300	11700	11300	10800	10400	10100	9700	9400	9100	8800	8500	8400
45.1 - 50.0	9400				14100	13400	12700	12100	11500	11000	10600	10100	9700	9400	9000	8700	8400	8200	7900	7700	7600
50.1 - 55.0	9000		14400	13600	12800	12100	11500	11000	10500	10000	9600	9200	9000	9000	9000	7900	7700	7400	7200	7000	
55.1 - 60.0	8600	14100	13200	12400	11700	11100	10600	10100	9600	9200	9000	9000	8900	8600	8300	7300	7000	6800	6600	6400	
60.1 - 65.0	7900	13000	11200	11200	10800	10300	9700	9300	9000	9000	8900	8500	8200	7900	7600						
65.1 - 70.0	7300	12100	11200	10700	10100	9500	9000	9000	8900	8600	8200	7900	7600	7300	7000						
70.1 - 75.0	6800	11300	10600	10000	9400	9000	9000	8700	8300	7900	7600	7300									
75.1 - 80.0	6300	10600	9900	9400	9000	8900	8500	8100	7700	7400	7100	6800									
80.1 - 85.0	5900	9900	9300	8800	8800	8400	8000														
85.1 - 90.0	5500	9400	9000	8300	8300	7900	7500														
90.1 - 95.0	5200	9000	8800	7900	7900	7400	7100														
95.1 - 100.0	4900	8900	8300	7500	7400	7000	6700														
100.1 - 105.0	4700	8400	7900	7100	7100	6700	6400														
105.1 - 110.0	4400	8000	7500	6800	6700	6400	6100														
110.1 - 115.0	4200	7600	7200	6500	6400	6100	5800														
115.1 - 120.0	4000	7300	6800	6200	6100	5800	5500														
120.1 - 125.0																					
125.1 - 130.0																					
130.1 - 135.0																					
135.1 - 140.0																					

^{*)} Minimum length when ordering one single plate is 3700 mm. Minimum order quantity is 2 plates when order length is less than 3700 mm.