


# Strenx® 1100 E/F

2025-09-03

The table shows available dimensions for direct order including the maximum length (mm).

 Some restrictions, contact your local sales representative for more information.

 Outside the range of dimensions.

Minimum length: 2000 mm<sup>\*)</sup>

Minimum quantities:

Thickness:

4.0 - 40.0

Minimum position weight:

2.5 tons

Width (mm)	1000-	1351-	1501-	1601-	1701-	1801-	1901-	2001-	2101-	2201-	2301-	2401-	2501-	2601-	2701-	2801-	2901-	3001-	3101-	3201-	3301-		
Thickness (mm)	1350	1500	1600	1700	1800	1900	2000	2100	2200	2300	2400	2500	2600	2700	2800	2900	3000	3100	3200	3300	3350		
3.0 - 3.9																							
4.0 - 4.7																							
4.8 - 5.7																							
5.8 - 6.0																							
6.1 - 6.7																							
6.8 - 7.7																							
7.8 - 8.7																							
8.8 - 10.0																							
10.1 - 25.0																							
25.1 - 26.0																							
26.1 - 27.0																							
27.1 - 28.0																							
28.1 - 29.0																							
29.1 - 30.0																							
30.1 - 31.0																							
31.1 - 32.0				Maximum length 14 630 mm																			
32.1 - 33.0	14200																						
33.1 - 34.0	13800																						
34.1 - 35.0	13400											14500											
35.1 - 36.0	13100											14100											
36.1 - 37.0	12700										14300	13700											
37.1 - 38.0	12400									14500	13900	13400											
38.1 - 39.0	12000									14200	13600	13000											
39.1 - 40.0	11700								14400	13800	13200	12700											
40.1 - 45.0																							
45.1 - 50.0																							
50.1 - 55.0																							
55.1 - 60.0																							
60.1 - 65.0																							
65.1 - 70.0																							
70.1 - 75.0																							
75.1 - 80.0																							

<sup>\*)</sup> Minimum length when ordering one single plate is 3700 mm. Minimum order quantity is 2 plates when order length is less than 3700 mm.